CSR-1000 CONCRETE BONDER

PREMIXED ACRYLIC FORMULATION

DESCRIPTION
CSR-1000 CONCRETE BONDER is a premixed acrylic formulation of a high quality butyl acrylic copolymer. Additional modifiers are incorporated to enhance the over-all strength potential as a concrete overlay system when used with CenturyStone cement/aggregate blends (i.e. CS-100, 500).

SOLIDS CONTENT: 100% ACRYLIC.

TYPICAL USES
CSR-1000 CONCRETE BONDER is an integral component in the CenturyStone Concrete Repair and Decorative Coating System.

When combined with CS-100 AGGREGATE BASE or CS-500 AGGREGATE TEXTURE the overlay can be applied as a base-coat, an acrylic lace texture, or various other trowelled finishes (i.e. tile, brick, flagstone, etc.) over properly prepared existing concrete substrates.

METHODS OF APPLICATION
As part of a complete overlay system, the CSR-1000 CONCRETE BONDER combined with CS-100 and 500 AGGREGATE blends can be applied by trowel, squeegee, screed, broom, brush or sponge. The consistency can be altered for a variety of repair or overlay applications.

PRIMARY FEATURES (as part of complete system)

· High Performance Concrete Technology
· 2" to Zero application thickness
· Re-pitch concrete surfaces (trip hazards, etc.)
· All-purpose base-coat
· Slip-resistant top coat (i.e. broom finish)
· Repairs broken concrete edges and spalls
· Cool walking surfaces
· Unlimited Decorative Applications
· Compatible with acrylic-based products
· Minimal drying time
· Suitable for interior or exterior
· High abrasion resistance

APPLICATION INSTRUCTIONS
DO NOT ADD WATER.
Add 1-2 gallons CSR-1000 CONCRETE BONDER to 1-50# bag of CS-100 or 500 AGGREGATE blends. Mix in a clean bucket with an electric operated masonry mixing paddle. Rinse off mixing paddle and tools with water immediately after use. Apply CSR-1000 to substrate as a primer before application.
Do not install at ambient temperatures below 40 degrees F.

COVERAGE
Coverage will vary with applications.

PACKAGING
5-gallon bucket
Pallet (36 buckets)

CenturyStone Concrete Products

www.CenturyStone.com • Mesa, AZ (480) 655-9733 fax: (480) 655-0651