

**CSR-200 “DURATHANE”
WATER-BORN URETHANE TOP-COAT**

DESCRIPTION

CSR-200 DURATHANE is a medium strength, chemical resistant, non-commercial, single component, formulation of 100% water based urethane. Additional modifiers are incorporated to enhance the durability of the solids and provide ease of application as a protective top coat over concrete surfaces and acrylic-modified concrete overlay systems (i.e. CenturyStone Concrete Coatings).

TYPICAL USES

CSR-200 DURATHANE is a stand alone product for non-commercial floor applications and serves as an integral component in the CenturyStone Concrete Repair and Decorative Coating System for non-commercial applications.

As a stand-alone top-coat the CSR-200 DURATHANE is excellent protection over clean concrete surfaces and newly installed concrete overlays. CSR-200 DURATHANE will provide good abrasion resistance, chemical resistance and has a high bond strength.

METHODS OF APPLICATION

CSR-200 DURATHANE is a single component, water-born product that can be applied by roller, brush, or industrial sprayer.

**PRIMARY FEATURES of CSR-200
DURATHANE**

- High Solids Formula – 32 % Solids
- Slip-resistant top coat (with resin sand)
- 12 color pallet
- Compatible with acrylic-based products
- Minimal drying time
- Suitable for interior or exterior
- Water clean-up
- Good abrasion resistance
- Good chemical resistance

APPLICATION INSTRUCTIONS

Pre-mixed solution. DO NOT DILUTE. Use a clean roller, or an industrial sprayer.

AVOID PUDDLING. Immediately brush or roll out puddles from drips, spills or over-spray to avoid build-up of unbonded acrylic solids. Rinse off tools with water immediately after use. Apply CSR-200 DURATHANE to properly prepared, clean surfaces.

Do not install at ambient temperatures below 40 degrees F.

COVERAGE

250-350 SF/gallon.

PACKAGING

- 2 - gallon pail
- 5 - gallon pail (36 pails/pallet)