

**CSR-890 “HIGH-TOP”
ACRYLIC-URETHANE ‘HYBRID’ TOP-COAT**

DESCRIPTION

CSR-890 HIGH TOP is a high strength, high chemical resistant, industrial, 2-component, hybrid formulation of acrylic/polyester-urethane. Additional modifiers are incorporated to enhance the durability of the acrylic solids and provide ease of application as a protective top coat over concrete surfaces and acrylic-modified concrete overlay systems (i.e. CenturyStone Concrete Coatings).

TYPICAL USES

CSR-890 HIGH TOP is a stand alone product for industrial and commercial floor applications including showroom floors, commercial kitchens and high traffic vehicle or walking surfaces.

As a stand-alone top-coat the CSR-890 HIGH TOP is excellent protection over clean concrete surfaces and newly installed concrete overlays. CSR-890 HIGH TOP will provide excellent abrasion resistance, UV resistance, chemical resistance and has extremely high bond strength.

METHODS OF APPLICATION

CSR-890 HIGH TOP is a 2-component product that can be applied by roller, brush, or industrial sprayer.

COVERAGE

180-250 SF/gallon.

PRIMARY FEATURES of CSR-890 HIGH TOP

- High Solids Formula – 90% Solids
- Industrial and Commercial application
- Slip-resistant top coat (with quartz aggregate)
- 12 color pallet
- Compatible with acrylic-based products
- Minimal drying time
- Suitable for interior or exterior
- Excellent UV resistance
- Excellent abrasion resistance
- Excellent chemical resistance
- VOC Compliant

APPLICATION INSTRUCTIONS

Mix in a clean bucket at a ratio of 2:1 part A to part B. Do not mix more than what can be applied in 20-30 minutes. Use a clean roller, or an industrial sprayer.

AVOID PUDDLING. Immediately brush or roll out puddles from drips, spills or over-spray to avoid build-up of unbonded acrylic solids. Clean tools with acetone immediately after use. Apply CSR-890 HIGH TOP to properly prepared, clean surfaces.

Do not install at ambient temperatures below 40 degrees F.

PACKAGING

- 1 ½ -gallon kit
- 3 – gallon kit
- 15 - gallon kit (36 pails/pallet)